



Art der Verkleidung		
KT	Kleinflansch	H1 DN1
L1	Flansch für Doppel-	H3 DN1
L2	klappenschleuse	
L4	siehe unser Maßblatt	
L6	Nr. 100-410	

Änderungen vorbehalten! Alle Maße in [mm]													bei 6 bar Druckluft			Motorischer Antrieb							
DN1	A	B	C	E	F	G	K	LK	d	z	H1	d1	Gew.	Schließdruck		Luftverbr							
														N	bar		NI/Spiel	E1	R	kg	U/min	kW	
150	380	450	305	375	380	310	150	220	M12	8	400	14		880	0,5	1,30							
200	450	520	350	430	460	390	230	270	M12	8	445	14		1592	0,5	2,53							
250	540	630	425	410	570	480	185	320	M12	8	520	14		2459	0,5	8,38							
300	600	690	460	550	640	550	170	370	M12	8	560	14		3527	0,5	13,40	834		14	21	0,25		
400	780	860	560	720	740	660	390	470	M12	12	690	14		6304	0,5	26,65							
500								580	M16	12		18			0,5								
600	1100	1220	800	1030	1120	1000	290	700	M16	16	885	18		14148	0,5	87,29							
700	1360	1500	910	995	1290	1170	280	800	M16	20	1165	18		19253	0,5	137,92							
800								900	M16	20		18			0,5								